



RELEASED
2011-08-25

D212-725-1-249 DOOR

NOTES:

- 1) MATERIAL: 6061-T6/T62 ALUMINUM SHEET, 0.063 THICK
PER QQ-A-250/11 OR AMS-QQ-A-250/11
OR AMS 4025 OR AMS 4027
OR ASTM B209
PER DART SPEC M6061T6S.063
OR 2024-T3 ALUMINUM SHEET, 0.063 THICK
PER QQ-A-250/4 OR AMS-QQ-A-250/4
OR AMS 4037
OR ASTM B209
PER DART SPEC M2024T3S.063
- 2) FINISH: CHEMICAL CONVERSION COAT PER DART QSI 005 4.1
- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
- 6) IDENTIFICATION: IDENTIFY PER QSI 044 6.1
- 7) WEIGHT: 1.16 lbs

A	NEW ISSUE	RF	11.02.24
REV.	DESCRIPTION	BY	DATE
DESIGN	RF	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
DRAWN	RF		
CHECKED		DRAWING NO.	REV. A
MFG. APPR.		D4183	SHEET 1 OF 1
APPROVED		TITLE	SCALE
DE APPR.		DOOR	NTS
DATE	11.02.24	COPYRIGHT © 2011 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.	